

# STILTREU



AGREEABLY IMPERFECT.  
ARCHITECTURAL,  
EXCITING AND SUBTLE.





**SUBTLY BALANCED “USED LOOK”. CHARMINGLY AUTHENTIC.  
BUT STATE-OF-THE-ART AND UNIVERSAL.**

Materials with character and soul are a current trend. Architecturally, they provide an exciting contrast to modern reduced design. They are like a soothing anchor for the soul. A foothold that provides space for honesty and authenticity. Age and usage are allowed to show here. With their strong character, they give rise to a sense of security. In a modern and subtle way. Suitably safe and true to the style.

# STILTREU USED LOOK. EXPRESSIVE. ACCENTUATED LINES.

## FIRINGS AND FORMATS



**452 silver-grey used look**  
Ø < 3 % - DIN EN 14411, Gr. A<sub>1</sub>

bar shape 490 x 40 x 14 mm



**454 creme-white used look**  
Ø < 3 % - DIN EN 14411, Gr. A<sub>1</sub>

bar shape 490 x 40 x 14 mm



**452 silver-grey used look**  
Ø < 3 % - DIN EN 14411, Gr. A<sub>1</sub>

DF



**454 creme-white used look**  
Ø < 3 % - DIN EN 14411, Gr. A<sub>1</sub>

DF

## PRODUCT DETAILS

### STILTREU

DIN EN 14411



format no.	7760	7756	7761	7757
description	clinker brick slips	clinker brick slips	corner <sup>1)</sup>	corner <sup>1)</sup>
nominal size (cm)	DF	bar shape	DF	bar shape
production size (mm)	240 x 52 x 14	490 x 40 x 14	240 x 115 x 52 x 14	240 x 115 x 40 x 14
452 silver-grey used look	★ PG 29 ●	★ PG 487 ●	★ PG 774 ●	★ PG 774 ●
454 creme-white used look				
pieces per bundle	18	18	14	21
pieces per m <sup>2</sup> /rm incl. joint	64,00	38,31	16,13	19,23
pieces per pallet	2.070	1.080	910	1.365
m <sup>2</sup> /rm per bundle	0,28	0,47	0,87	1,09
m <sup>2</sup> /rm per pallet	32,34	28,19	56,42	70,98
bundles per pallet	115	60	65	65
kg per pallet	826	670	519	566
kg per piece	0,399	0,620	0,570	0,415
kg per m <sup>2</sup> /rm	25,536	23,752	9,194	7,980
kg per bundle	7,182	11,160	7,980	8,715
surcharge	❖	❖	❖	❖

★ = Discount on pallets. ● = Normally available ex stock. PG = Price group (please see current price list). ❖ = Minimum quantity: each open box will incur a surcharge.

<sup>1)</sup> = The Ströher standard for angular accuracy in angled brick slips is based on the DIN 105 standard for exposed clinker brickwork, but with only 50% of the permissible tolerance values. The Ströher specification is thus +/- 1°. This equates to a maximum deviation of +/- 4 mm on the stretcher side and +/- 2 mm on the header side for a corner with the 240 x 115 mm format.

The formats shown are illustrative drawings and are not binding. All information without guarantee.

\* Ströher is the only German manufacturer offering a 25-year frost resistance guarantee on the following extruded products that have been correctly installed by a qualified professional tiler: Keraplatte® Selected, Keraplatte® Zoé, Keraplatte® Gravel Blend, Keraplatte® Epos, Keraplatte® Aera T, Keraplatte® Aera, Keraplatte® Roccia X, Keraplatte® Roccia, Keraplatte® Asar, Keraplatte® Terra, Keraplatte® Duro, Terrace slab TerioTec® X Profile, Terrace slab TerioTec® X, Terrace Slab TerioTec®, Stalotec®, Brickwerk, Brick 60, Wasserbrand, Kontur, Stiltreu, Riegel 50, Handstrich, Steinlinge, Glanzstücke, Zeitlos, Keraprotect® and Keravette®. Please find further explanations in our general terms and conditions.



Completely frost-resistant  
\*25 year guarantee



Tunnel kiln fired



Suitable for  
insulation systems



Wheatproof



Economic



In compliance  
with DIN EN



Fade-free and  
colourfast



Easy maintenance  
and hygienic



Ecofriendly



Resistant to  
chemicals



Glow-resistant  
and fireproof



Anti-static